

IN THE CLAIMS

Please amend the claims as follows:

1. (previously presented): A heat exchanger comprising:

a partition type heat transfer material for parting a high temperature fluid and a low temperature fluid from each other, wherein

the heat transfer material is bellow-shaped and is arranged such that both the fluids flow parallel or counter to each other mainly through a gap portion in the bellows section of the heat transfer material along the ridge line or valley line thereof,

the heat transfer material separates the high temperature fluid and the low temperature fluid from each other throughout the heat exchanger, and

the cross sectional area of the gap portion changes along the flow path of the fluids.

2. (currently amended): A self-heat exchange type heat exchanger comprising:

(a) a partition type heat transfer material for parting a high temperature fluid and a low temperature fluid from each other, wherein

the heat transfer material is bellow-shaped and is arranged such that both the fluids flow counter to each other mainly through a gap portion in the bellows section of the heat transfer material along the ridge line or valley line thereof,

the heat transfer material has a fluid forwarding space portion at one or both ends thereof crossing the ridge line of the bellows section for forwarding one of the fluids to the gap portion in the bellows section on the opposite side thereof, and

the fluid which has been forwarded to the opposite side via the fluid forwarding space portion acts as the other fluid to be heat-exchanged to perform heat exchange; and

(b) at least one air-permeable structure, different from the heat transfer material, provided in the gap portion of the bellows section of the heat transfer material, wherein

~~a functional material selected from the group of an adsorbent and a heat storage material is provided in the gap portion of the bellows section of the heat transfer material as the air-permeable structure, different from the heat transfer material, or supported on the air-permeable structure, different from the heat transfer material~~

the air-permeable structure acts as a spacer,

as the heat transfer material there is used one having no air permeability,

the self-heat exchange type heat exchanger is formed by the heat transfer material, a structure for spacer and a filter cloth in combination,

the structure extends beyond the end of the fluid forwarding space portion of the heat transfer material, and

a filter cloth is formed therearound in the form of bellows.

3. (currently amended): A reactor comprising:

(a) a self-heat exchange type heat exchanger having a partition type heat transfer material for parting a high temperature fluid and a low temperature fluid from each other, wherein

the heat transfer material is bellows-shaped and is arranged such that both the fluids flow counter to each other mainly through a gap portion in the bellows section of the heat transfer

material along the ridge line or valley line thereof and the heat transfer material has fluid forwarding space portion at one or both ends thereof crossing the ridge line of the bellows section for forwarding one of the fluids to the gap portion in the bellows section on the opposite side thereof, and

the fluid which has been forwarded to the opposite side via the fluid forwarding space portion acts as the other fluid to be heat-exchanged to perform heat exchange;

(b) a heating element or heat-absorbing element provided in the fluid forwarding space portion of the heat exchanger; and

(c) at least one air-permeable structure, different from the heat transfer material, provided in the gap portion of the bellows section of the heat transfer material, ~~wherein~~

~~a functional material selected from the group of an adsorbent and a heat storage material is provided in the gap portion of the bellows section of the heat transfer material as the air-permeable structure, different from the heat transfer material, or supported on the air-permeable structure, different from the heat transfer material;~~

(d) a particle removing filter for catching and removing fine particles provided in close contact with the side of the heat transfer material of the heat exchanger to which the fluid is forwarded.

4. (canceled)

5. (canceled)

6. (canceled)

7. (canceled)

8. (currently amended): ~~The reactor as described in Claim 3A~~ a reactor comprising:

(a) a self-heat exchange type heat exchanger having a partition type heat transfer material for parting a high temperature fluid and a low temperature fluid from each other, wherein the heat transfer material is bellows-shaped and is arranged such that both the fluids flow counter to each other mainly through a gap portion in the bellows section of the heat transfer material along the ridge line or valley line thereof and the heat transfer material has fluid forwarding space portion at one or both ends thereof crossing the ridge line of the bellows section for forwarding one of the fluids to the gap portion in the bellows section on the opposite side thereof, and

the fluid which has been forwarded to the opposite side via the fluid forwarding space portion acts as the other fluid to be heat-exchanged to perform heat exchange;

(b) a heating element or heat-absorbing element provided in the fluid forwarding space portion of the heat exchanger; and

(c) at least one air-permeable structure, different from the heat transfer material, provided in the gap portion of the bellows section of the heat transfer material, wherein

a functional material selected from the group of an adsorbent and a heat storage material  
is provided in the gap portion of the bellows section of the heat transfer material as the air-  
permeable structure, different from the heat transfer material, or supported on the air-permeable  
structure, different from the heat transfer material, wherein and

the heat transfer material includes a filtrating function allowing gas permeation and  
particle catch.

9. (currently amended): A radiation heater comprising:

(a) a self-heat exchange type heat exchanger having a partition type heat transfer material  
for parting a high temperature fluid and a low temperature fluid from each other, wherein

the heat transfer material is bellows-shaped and is arranged such that both the fluids flow  
counter to each other mainly through a gap portion in the bellows section of the heat transfer  
material along the ridge line or valley line thereof, and

the heat transfer material has a fluid forwarding space portion at one or both ends thereof  
crossing the ridge line of the bellows section for forwarding one of the fluids to the gap portion  
in the bellows section on the opposite side thereof, and

the fluid which has been forwarded to the opposite side via the fluid forwarding space  
portion acts as the other fluid to be heat-exchanged to perform heat exchange; and

(b) a burner disposed in the fluid forwarding space portion of the heat exchanger, wherein  
the wall parting the fluid forwarding space portion in which the burner is disposed from  
the exterior is formed by a heat radiating plate, and

heat generated in the fluid forwarding space portion is radiated to outside the radiation heater by the heat radiating plate.

10. (currently amended): A radiation heater comprising:

(a) a self-heat exchange type heat exchanger having a partition type heat transfer material for parting a high temperature fluid and a low temperature fluid from each other, wherein

the heat transfer material is bellows-shaped and is arranged such that both the fluids flow counter to each other mainly through a gap portion in the bellows section of the heat transfer material along the ridge line or valley line thereof, and

the heat transfer material has a fluid forwarding space portion at one or both ends thereof crossing the ridge line of the bellows section for forwarding one of the fluids to the gap portion in the bellows section on the opposite side thereof, and

the fluid which has been forwarded to the opposite side via the fluid forwarding space portion acts as the other fluid to be heat-exchanged to perform heat exchange; and

(b) an exothermic reaction-accelerating catalyst supported on the entire surface of the heat transfer material of the heat exchanger or the surface thereof in the vicinity of the fluid forwarding space portion, wherein

the wall parting the fluid forwarding space portion from the exterior is formed by a heat radiating plate and as the fluid there is used one including the reactive components, and

heat generated in the fluid forwarding space portion is radiated to outside the radiation heater by the heat radiating plate.

11. (canceled)

12. (canceled)

13. (canceled)

14. (canceled)

15. (canceled)

16. (canceled)

17. (canceled)

18. (canceled)

19. (currently amended): The self-heat exchange type heat exchanger as described in Claim  
~~17~~ 2, wherein

the surface of the heat transfer material is partly opened to form a fluid forwarding space portion, or the end of the heat transfer material is partly cut away to form a fluid forwarding space portion.

20. (original): The reactor as described in Claim 8, wherein

the heat transfer material having a filtrating function is retained and formed in the form of a structure for spacer in the form of bellows.

21. (previously presented): The heat exchanger as described in claim 1, further comprising:

a functional material selected from the group of an adsorbent and a heat storage material provided in the gap portion of the bellows section of the heat transfer material separately of the heat transfer material.

22. (previously presented): The radiation heater as described in claim 9, further comprising:

a functional material selected from the group of an adsorbent and a heat storage material provided in the gap portion of the bellows section of the heat transfer material separately of the heat transfer material.

23. (previously presented): The radiation heater as described in claim 10, further comprising:



a functional material selected from the group of an adsorbent and a heat storage material provided in the gap portion of the bellows section of the heat transfer material separately of the heat transfer material.

24. (canceled)